



### 40ft 3-axle Skeleton Semi Trailer with Bpw 13t Axle

As the professional manufacturer JUPITER TRAILER, we would like to provide you 40FT 2-AXLE SKELETON SEMI TRAILER. And we will offer you the best quotation with quality assured and timely delivery. JUPITER® is a large-scale semi trailer and special vehicles manufacturer and supplier in China. We have been specialized in semi trailer and special vehicles for more than 39 years. Our 40ft 3-axle Skeleton Semi Trailer with Bpw 13t Axle have a good price and quality advantage and had already exported to the Asia, Africa and South America countries. We look forward to becoming your long-term partner in China

### Product Description

This JUPITER® 40ft 3-axle Skeleton Semi Trailer with Bpw 13t Axle is suitable for carrying ISO 20FT and 40FT containers, which are mostly used in the port, pier and container yards. 40ft 2-axle skeleton semi trailer is the best choice for the transportation and operation of 20ft and 40ft container van box with high efficiency and economic return, we use famous brand parts on 40ft 2-axle skeleton semitrailer, such as FUWA or BPW Brands Axle, JOST King Pin.so we recommend the end users or drivers to choose this 40ft 2-axle skeleton semi trailer with Fuwa 13T axle and welcome to inquiry about our 40ft 2-axle skeleton semi trailer.

## JUPITER® 40FT 2-AXLE SKELETON SEMI TRAILER Parameter (Specification)

Specification:	
Type:	40FT 2 Axles Skeleton Trailer
Model:	JPT9352TJZG
Dimension:	
Length:	12,420mm
Width:	2,480mm
Height:	1,540mm

Wheel Base:	8800+1310mm
<b>Frame &amp; Structure:</b>	
Main beam:	Material Q345B. Fabricated "H" beam height 500mm, Top flange thickness 12mm, Middle web thickness 6mm, Bottom flange thickness 14mm
Side beam:	14# channel steel
Platform:	2.5mm thick diamond plate with supporting channel, 4 lines 40*30 shaped steel
Kingpin:	2'(50#), bolted in type
Twist lock:	8sets twist locks
Welding standard:	All welding are to be done by qualified welder per applicable national standard
Painting:	Shot blast at Standard SA 2.5 prior to application of primer, polyurethane top coat. Total DFT not less than 100um
<b>Running gear:</b>	
Suspension:	mechanical suspension, heavy duty leaf spring 10x13mmx90mm, China
Axle:	Fuwa brand 2pcs*13 ton capacity, China
Brake system:	Dual line pneumatic brake, SAE hose and connector, without ABS
Brake chamber:	2 units T30/30 spring brake chambers, 2 units T30 brake chambers
Air tank:	40L, 1pc, China
Tire:	11R22.5, 8 + 1 pcs. China
Rim:	8.25*22.5 steel disc wheel, 10 holes ISO, 8+1 pcs. China
Landing gear:	Fuwa 28T two speed telescopic manual landing gear
<b>Electrical System:</b>	
Voltage:	24 Volt
Receptacle:	7 way socket SAE standard, China
Front marker	White

lamp:	
Side marker lamp:	White & Red
Rear lamp:	Red
Turn signal lamp:	Amber
Reflector:	Per customer requirement
Wiring:	Electric cable protected by PVC conduit on main frame
<b>Accessories:</b>	
Mud guard:	Steel mud guard
Spare wheel carriers:	1 pc
Tool box:	1 pc
<p>Note: All the details not mentioned above should comply with Chinese regulations. If any component or structure changed, the price shall be modified accordingly.</p>	